



## PRO|EDGE Z201DU DISPLAY & DVI ZERO CLIENT

**An ideal solution**  
for meeting VDI demands in multiple industries.

I-O Corporation's flagship product, Pro|Edge Z201DU is a high-performing solution that was specifically designed to help your company meet its virtual desktop infrastructure needs. This product, which works best in an established VMware® environment, provides users with ready-access to a familiar virtual desktop anytime, anywhere, and also offers dual-monitor support to help them increase their productivity. Moreover, **It features the Tera2321 PC-over-IP (PCoIP) portal processor**, allowing for greater efficiency, performance, and security with cloud computing. Plus, it offers one Display port and one DVI port support and six USB ports.

This solution is an excellent choice for meeting wide variety of VDI end user and business needs in education, financial services, government, healthcare, and any other industry or environment where PCoIP Zero clients are required.

For more information or to request a 30-day free trial, **visit [www.iocorp.com](http://www.iocorp.com)** or call **(800) 871-9998**

### Benefits

**HIGH-PERFORMING SOLUTION:**

A reliable solution that offers a high processing speed and high resolution.

**GREATLY INCREASES NETWORK SECURITY:**

Securely delivers applications to end users in a cloud computing environment.

**PROVIDES USERS WITH A FAMILIAR DESKTOP EXPERIENCE:**

Enables users to access their desktop anytime, anywhere.

**EASY TO DEPLOY, MANAGE, AND USE:**

Can be easily and seamlessly integrated into an existing VMware® infrastructure. No configuration, required. Moreover, the solution greatly reduces the need to manage images, firmware, and settings.

**LONG LIFE EXPECTANCY:**

Minimal space requirements. Durable solution with fan-less, rugged, integrated cooling.

**ENERGY EFFICIENT**

Low power consumption.

**COST-EFFECTIVE:**

Competitively priced.

**FIVE-YEAR WARRANTY:**

Comes with a five-year limited warranty and unlimited customer support and service.



# SPECIFICATIONS

<b>VMWARE® READY</b>	VMware-certified hardware
<b>MAIN BOARD</b>	Processor: Tera2321 PCoIP portal processor Process: 65nm G-Process CMOS
<b>MEMORY</b>	System: 512MB DDR3 (32-bit 667Mhz) Flash: 256Mbit of parallel flash
<b>GRAPHICS</b>	Max resolution: 2560x1600 Standard resolution: Dual-screen @ 1920x1200 Color: Depth: 8, 15, 16, 24bpp Image performance: 150 Mpps Max screens: 2
<b>I/O INTERFACES</b>	Video: 1 x DVI and 1 x DP I/O ports: 6 x USB 2.0 (4-front / 2-back) Speaker / mic / headphone: 3.5mm Jack
<b>NETWORKING</b>	Gigabit ethernet: Ethernet 10/100/1000 Mb/s - RJ-45
<b>ENVIRONMENT</b>	Cooling: Fanless - Integrated passive heat sink Operating noise: No noise Operating temperature: 0°C - ~ 35°C Non-operating temperature: -30°C - ~ 60°C Operating humidity: 10% - ~ 90% (Non-condensing) Non-operating humidity: 5% - ~95% (Non-condensing) Dimensions / weight: 6.8 x 5.2 x 1.1 in / 1.79 lbs Locking port: Integrated Kensington security slot Mounting: VESA mount compliant
<b>AC ADAPTER</b>	Operating voltage range: 100 - ~240 VAC Rated line frequency: 50 - 60 Hz Rated output current (max): 3A Output voltage: 12 V DC
<b>ENERGY</b>	Consumption: 8 W @ idle (36W with 6-USB attached) Wake / sleep: Wake on LAN / USB support Power failure: Power-on after power-fail
<b>SOFTWARE</b>	Operating system: O/S independent Regulatory: CS, FCC, CE, CCC, C-Tick, KCC, GOST, UL Firmware: Free updates available online

